Serial No. 10/087,925 Docket No. T36-143020M/KOH

AMENDMENTS TO THE CLAIMS:

- 1. (Previously presented) A light-emitting device comprising:
 - a light-emitting element;
- a case comprising a cup-like portion having a bottom on which said light-emitting element is mounted;
- a sealing member with which said cup-like portion is filled so that said light-emitting element is covered with said sealing member; and
- a low-refractive-index layer having a refractive index lower than that of said sealing member and formed between said sealing member and a surface of said case shaping a side surface of said cup-like portion,

wherein said low-refractive-index layer comprises a gap between said sealing member and said surface of said case, and

wherein said gap has an end on an emission observation surface side, said end being filled with a light-transmissible material.

2-3. (Canceled)

- 4. (Currently amended) A light-emitting device comprising:
 - a light-emitting element;
- a case comprising a cup-like portion having a bottom on which said light-emitting element is mounted;
- a sealing member with which said cup-like portion is filled so that said light-emitting element is covered with said sealing member; and
- a low-refractive-index layer having a refractive index lower than that of said sealing member and formed between said sealing member and a surface of said case shaping a side surface of said cup-like portion,

wherein, on the bottom side of said cup-like portion, said sealing member adheres to said surface of said case

wherein said sealing member adheres to said bottom of said cup-like portion.

Serial No. 10/087,925 Docket No. T36-143020M/KOH

- 5. (Previously presented) A light-emitting device according to claim 1, wherein said surface of said case comprises a reflective surface.
- 6. (Previously presented) A light-emitting device according to claim 1, wherein said sealing member comprises at least one material selected from the group consisting of silicone resin, epoxy resin, urea resin, and glass.
- 7. (Canceled)
- 8. (Previously presented) A light-emitting device comprising:
 - a light-emitting element;
- a case comprising a cup-like portion having a bottom on which said light-emitting element is mounted;
- a sealing member with which said cup-like portion is filled so that said light-emitting element is covered with said sealing member; and
- a low-refractive-index layer having a refractive index lower than that of said sealing member and formed between said sealing member and a surface of said case shaping a side surface of said cup-like portion,

wherein said sealing member comprises one of grains and fine particles of a light-transmissible material, and

wherein said one of said grains and fine particles are localized on the bottom side of said cup-like portion.

- 9. (Previously presented) A light-emitting device according to claim 8, wherein said one of said grains and fine particles comprises a linear expansion coefficient smaller than that of said sealing member.
- 10. (Previously presented) A light-emitting device according to claim 1, wherein said sealing member comprises a fluorescent substance.

11-13. (Canceled)

Serial No. 10/087,925 Docket No. T36-143020M/KOH

- 14. (Previously presented) A light-emitting device according to claim 1, wherein said light-emitting element comprises at least one Group III nitride compound semiconductor layer.
- 15. (Canceled)
- 16. (Previously presented) A light-emitting device according to claim 1, wherein an angle between said side surface of said cup-like portion and an optical axis is in a range from 20 to 60 degrees.
- 17. (Previously presented) A light-emitting device according to claim 1, wherein said lighting element comprises a flip chip light-emitting diode.
- 18. (Previously presented) A light-emitting device according to claim 1, wherein a difference between a refractive index of said sealing member and a refractive index of said low-refractive-index layer is at least 0.4.
- 19. (Currently amended) A light-emitting device according to claim 1, wherein <u>a said</u> shrinkage <u>of said sealing member</u> is selectively suppressed in an area of said bottom of said cup-like portion.
- 20. (Previously presented) A light-emitting device according to claim 1, wherein said side-surface of said cup-like portion comprises one of aluminum and silver.
- 21. (Previously presented) A light-emitting device according to claim 1, further comprising:

a lead frame which defines said bottom of said cup-like portion, said light-emitting element being formed on said lead frame.